

Date Form Completed:	
Completed by: ———	

Provision C.3 Data Form

All projects that create and/or replace 10,000 sq. ft. or more of impervious surface on the project site must fill out this worksheet and submit it with the development project application. All restaurants, auto service facilities, retail gasoline outlets, and uncovered parking lot projects (stand-alone or part of another development project, including the top uncovered portion of parking structures) that create and/or replace 5,000 sq. ft. or more of impervious surface on the project site must also fill out this worksheet. Interior remodeling projects, routine maintenance or repair projects such as re-roofing and re-paving, and single family homes that are not part of a larger plan of development are NOT required to complete this worksheet. What is an Impervious Surface? An impervious surface is a surface covering or pavement that prevents the land's natural ability to absorb and infiltrate rainfall/stormwater. Impervious surfaces include, but are not limited to rooftops, walkways, paved patios, driveways, parking lots, storage areas, impervious concrete and asphalt, and any other continuous watertight pavement or covering. Pervious pavement, underlain with pervious soil or pervious storage material (e.g., drain rock), that infiltrates rainfall at a rate equal to or greater than surrounding unpaved areas OR that stores and infiltrates the water quality design volume specified in Provision C.3. d of the Municipal Regional Stormwater Permit (MRP), is not considered an impervious surface. For More Information For more information regarding selection of Best Management Practices for stormwater pollution prevention or stormwater treatment contact: 1. Project Information Project Phase(s): Of	Which Projects Must Comply with Stormwater Requirements?
(stand-alone or part of another development project, including the top uncovered portion of parking structures) that create and/or replace 5,000 sq. ft. or more of impervious surface on the project site must also fill out this worksheet. Interior remodeling projects, routine maintenance or repair projects such as re-roofing and re-paving, and single family homes that are not part of a larger plan of development are NOT required to complete this worksheet. What is an Impervious Surface? An impervious surface is a surface covering or pavement that prevents the land's natural ability to absorb and infiltrate rainfall/stormwater. Impervious surfaces include, but are not limited to rooftops, walkways, paved patios, driveways, parking lots, storage areas, impervious concrete and asphalt, and any other continuous watertight pavement or covering. Pervious pavement, underlain with pervious soil or pervious storage material (e.g., drain rock), that infiltrates rainfall at a rate equal to or greater than surrounding unpaved areas OR that stores and infiltrates the water quality design volume specified in Provision C.3.d of the Municipal Regional Stormwater Permit (MRP), is not considered an impervious surface. For More Information For more information regarding selection of Best Management Practices for stormwater pollution prevention or stormwater treatment contact: 1. Project Information Project Name:	All projects that create and/or replace 10,000 sq. ft. or more of impervious surface on the project site must
single family homes that are not part of a larger plan of development are NOT required to complete this worksheet. What is an Impervious Surface? An impervious surface is a surface covering or pavement that prevents the land's natural ability to absorb and infiltrate rainfall/stormwater. Impervious surfaces include, but are not limited to rooftops, walkways, paved patios, driveways, parking lots, storage areas, impervious concrete and asphalt, and any other continuous watertight pavement or covering. Pervious pavement, underlain with pervious soil or pervious storage material (e.g., drain rock), that infiltrates rainfall at a rate equal to or greater than surrounding unpaved areas OR that stores and infiltrates the water quality design volume specified in Provision C.3.d of the Municipal Regional Stormwater Permit (MRP), is not considered an impervious surface. For More Information For more information regarding selection of Best Management Practices for stormwater pollution prevention or stormwater treatment contact: 1. Project Information Project Address: Cross Streets: Applicant/Developer Name: Project Phase(s): Of Engineer: Project Type (Check all that apply): New Development Redevelopment Private Private Public Residential Commercial Industrial Mixed Use Institutional	(stand-alone or part of another development project, including the top uncovered portion of parking structures) that create and/or replace 5,000 sq. ft. or more of impervious surface on the project site must also
An impervious surface is a surface covering or pavement that prevents the land's natural ability to absorb and infiltrate rainfall/stormwater. Impervious surfaces include, but are not limited to rooftops, walkways, paved patios, driveways, parking lots, storage areas, impervious concrete and asphalt, and any other continuous watertight pavement or covering. Pervious pavement, underlain with pervious soil or pervious storage material (e.g., drain rock), that infiltrates rainfall at a rate equal to or greater than surrounding unpaved areas OR that stores and infiltrates the water quality design volume specified in Provision C.3.d of the Municipal Regional Stormwater Permit (MRP), is not considered an impervious surface. For More Information For more information regarding selection of Best Management Practices for stormwater pollution prevention or stormwater treatment contact: 1. Project Information Project Address: Cross Streets: Applicant/Developer Name: Project Phase(s): of Engineer: Project Type (Check all that apply): \(\text{ New Development } \) Redevelopment \(\text{ Private } \) Public \(\text{ Residential } \) Commercial \(\text{ Industrial } \) Mixed Use \(\text{ Institutional } \) \(\text{ Residential } \) Commercial \(\text{ Industrial } \) Mixed Use \(\text{ Institutional } \)	single family homes that are not part of a larger plan of development are NOT required to complete this
An impervious surface is a surface covering or pavement that prevents the land's natural ability to absorb and infiltrate rainfall/stormwater. Impervious surfaces include, but are not limited to rooftops, walkways, paved patios, driveways, parking lots, storage areas, impervious concrete and asphalt, and any other continuous watertight pavement or covering. Pervious pavement, underlain with pervious soil or pervious storage material (e.g., drain rock), that infiltrates rainfall at a rate equal to or greater than surrounding unpaved areas OR that stores and infiltrates the water quality design volume specified in Provision C.3.d of the Municipal Regional Stormwater Permit (MRP), is not considered an impervious surface. For More Information For more information regarding selection of Best Management Practices for stormwater pollution prevention or stormwater treatment contact: 1. Project Information Project Address: Cross Streets: Applicant/Developer Name: Project Phase(s): of Engineer: Project Type (Check all that apply): \(\text{ New Development } \) Redevelopment \(\text{ Private } \) Public \(\text{ Residential } \) Commercial \(\text{ Industrial } \) Mixed Use \(\text{ Institutional } \) \(\text{ Residential } \) Commercial \(\text{ Industrial } \) Mixed Use \(\text{ Institutional } \)	What is an Impervious Surface?
For more information regarding selection of Best Management Practices for stormwater pollution prevention or stormwater treatment contact: 1. Project Information Project Name: APN # Project Address: Cross Streets: Applicant/Developer Name: Project Phase(s): ofEngineer: Project Type (Check all that apply): New Development Private Private Public Residential Commercial Industrial Mixed Use Institutional Restaurant Uncovered Parking Retail Gas Outlet Auto Service (SIC code) [SOLO SOLA SOLA SOLA SOLA SOLA SOLA SOLA	infiltrate rainfall/stormwater. Impervious surfaces include, but are not limited to rooftops, walkways, paved patios, driveways, parking lots, storage areas, impervious concrete and asphalt, and any other continuous watertight pavement or covering. Pervious pavement, underlain with pervious soil or pervious storage material (e.g., drain rock), that infiltrates rainfall at a rate equal to or greater than surrounding unpaved areas OR that stores and infiltrates the water quality design volume specified in Provision C.3.d of the Municipal
For more information regarding selection of Best Management Practices for stormwater pollution prevention or stormwater treatment contact: 1. Project Information Project Name: APN # Project Address: Cross Streets: Applicant/Developer Name: Project Phase(s): ofEngineer: Project Type (Check all that apply): New Development Private Private Public Residential Commercial Industrial Mixed Use Institutional Restaurant Uncovered Parking Retail Gas Outlet Auto Service (SIC code) [SOLO SOLA SOLA SOLA SOLA SOLA SOLA SOLA	For More Information
Project Name:	For more information regarding selection of Best Management Practices for stormwater pollution prevention
Project Address: Cross Streets: Applicant/Developer Name: Project Phase(s):of Engineer: Project Type (Check all that apply): □ New Development □ Redevelopment □ Private □ Public □ Residential □ Commercial □ Industrial □ Mixed Use □ Institutional □ Restaurant □ Uncovered Parking □ Retail Gas Outlet □ Auto Service (SIC code)	
Cross Streets: Applicant/Developer Name: Project Phase(s): of Engineer: Project Type (Check all that apply): □ New Development □ Redevelopment □ Private □ Public □ Residential □ Commercial □ Industrial □ Mixed Use □ Institutional □ Restaurant □ Uncovered Parking □ Retail Gas Outlet □ Auto Service (SIC code)	Project Name:APN #
Applicant/Developer Name: Project Phase(s): of Engineer: Project Type (Check all that apply): □ New Development □ Redevelopment □ Private □ Public □ Residential □ Commercial □ Industrial □ Mixed Use □ Institutional □ Restaurant □ Uncovered Parking □ Retail Gas Outlet □ Auto Service (SIC code)	Project Address:
Applicant/Developer Name: Project Phase(s): of Engineer: Project Type (Check all that apply): □ New Development □ Redevelopment □ Private □ Public □ Residential □ Commercial □ Industrial □ Mixed Use □ Institutional □ Restaurant □ Uncovered Parking □ Retail Gas Outlet □ Auto Service (SIC code)	Cross Streets:
Project Phase(s):of Engineer:	
Project Type (Check all that apply): □ New Development □ Redevelopment □ Private □ Public □ Residential □ Commercial □ Industrial □ Mixed Use □ Institutional □ Restaurant □ Uncovered Parking □ Retail Gas Outlet □ Auto Service (SIC code)	
□ Private □ Public □ Residential □ Commercial □ Industrial □ Mixed Use □ Institutional □ Restaurant □ Uncovered Parking □ Retail Gas Outlet □ Auto Service (SIC code)	
☐ Residential ☐ Commercial ☐ Industrial ☐ Mixed Use ☐ Institutional ☐ Restaurant ☐ Uncovered Parking ☐ Retail Gas Outlet ☐ Auto Service (SIC code)	
(5012 5014 5541 7522 7524 7520 7520)	
Other	☐ Restaurant ☐ Uncovered Parking ☐ Retail Gas Outlet ☐ Auto Service (SIC code) (5013-5014, 5541, 7532-7534, 7536-7539)
Project Description:	110ject Description.

2. Project Size

2. Project Size a. Total Site Area:acres		b. Total Site Area Disturbed:			acres	
Site Totals	Total Existing (Pre-project) Area (ft²)	Existing Area Retained ¹ (ft ²)	g, grading, or excavat Existing Area Replaced ² (ft ²)	New Area Created ² (ft ²)	Total Post- Project Area (ft ²	
c. Total Impervious Area (IA)	THE (IV)					
d. Total new and replaced imper	vious area					
e. Total Pervious Area (PA) ³						
f. Total Area (IA+PA)						
g. Percent Replacement of IA in	Redevelopment Proj	ects: (Existing IA	Replaced ÷ Existir	ng Total IA) x 10	0%%	
https://www.v		verage under th	e State Construc	r/construction.h	<u>tml</u>)	
☐ Yes, C.3. sou ☐ No, C.3. sour b. For redevelopme ☐ Yes, C.3. require treatment) ap ☐ No, C.3. require. C. Does the project	10,000 sq. ft. or mas outlets, and state outlets, and state of ce control, site of the control and site of the projects, is #2.5 uirements (site desply to the entire statements only approximation)	and-alone uncovered lesign and treatment to design require general to 50% esign and source site ply to the imperace 5,000 sf or	vered parking? ment requirement ements may app or more? e control, as app rvious area creat more of impervi	nts apply ly – check with ropriate, and st ed and/or repla ous surface par	n local agency tormwater aced rking?	
b. Is the project lo Map? (www.sc	t create and/or repoervious area grea	olace one acre on ter than the pre f HM applicabilismap)	or more of imper -project (existin No – exempt fro lity (green area)	g) impervious on HM, go to p	area? page 3	

 $^{^{1}}$ "Retained" means to leave existing IA in place. An IA that goes through maintenance (e.g., pavement resurfacing/slurry seal/grind), but no change in grade is considered "retained".

SCVURPPP C.3. Data Form Page 2 of 4 September 2019

² The "new" and "replaced" IA are based on the total area of the site and not specific locations on site. For example, impervious parking created over a pervious area is not "new" IA, if an equal amount of pervious area replaces IA somewhere else on the site. Constructed IA on a site that does not exceed the total pre-project IA will be considered "replaced" IA. A site will have "new" IA only if the total post-project IA exceeds the total pre-project IA (total post-project IA – total pre-project IA = New IA).

³ Include bioretention areas, infiltration areas, green roofs, and pervious pavement in PA calculations.

6. Selection of Specific Stormwater Control Measures: **Site Design Measures Source Control Measures Treatment Measures** ☐ Minimize land disturbed ☐ Wash area/racks, drain to ☐ None (all impervious (e.g., protect trees and soil) sanitary sewer⁵ surface drains to selfretaining areas) ☐ Minimize impervious ☐ Covered dumpster area, surfaces (e.g., reduction in drain to sanitary sewer⁶ LID Treatment post-project impervious ☐ Sanitary sewer connection ☐ Bioretention area surface) or accessible cleanout for ☐ Flow-through planter ☐ Minimum-impact street or swimming ☐ Tree Well Filter or Trench parking lot design (e.g., pool/spa/fountain⁶ with bioretention soils parking on top of or under ☐ Beneficial landscaping ☐ Rainwater harvest/use (e.g., buildings) (minimize irrigation, runoff, cistern or rain barrel for ☐ Cluster structures/ pavement pesticides and fertilizers; designated use, sized for promotes treatment) C.3.d treatment) ☐ Disconnected downspouts (direct runoff from roofs, ☐ Outdoor material storage ☐ Infiltration trench sidewalks, patios to protection ☐ Infiltration well/dry well landscaped areas) ☐ Covers, drains for loading ☐ Subsurface Infiltration ☐ Pervious pavement docks, maintenance bays, System (e.g. vault or large fueling areas diameter conduit over drain ☐ Green roof rock) ☐ Maintenance (pavement ☐ Other self-treating⁴ area Other sweeping, catch basin (e.g., landscaped areas) cleaning, good housekeeping) ☐ Self-retaining⁴ area Non-LID Treatment Methods \Box Interceptor trees³ ☐ Storm drain labeling ☐ Proprietary high flow rate tree box filter⁷ ☐ Rainwater harvesting and ☐ Other use (e.g., rain barrel, cistern ☐ Proprietary high flow media for designated use)⁵ filter (sand, compost, or proprietary media)⁷ ☐ Preserved open space: ☐ Vegetated filter strip⁸ _____ ac. or sq. ft. (circle ☐ Extended detention basin⁸ one) ☐ Vegetated swale⁸ ☐ Protected riparian and wetland areas/buffers □ Other (Setback from top of bank: ____ft.) ☐ Other _____ Flow Duration Controls for Hydromodification Management (HM) □ Extended ☐ Underground tank or ☐ Bioretention with outlet □ Other Detention basin vault control

⁴ See SCVURPPP C3 Handbook for definitions. <u>https://scvurppp.org/2016/06/20/c-3-stormwater-handbook-june-2016/</u>

⁵ Optional site design measure; does not have to be sized to comply with Provision C.3.d treatment requirements.

⁶ Subject to sanitary sewer authority requirements.

⁷ These treatment measures are only allowed if the project qualifies as a "Special Project".

⁸ These treatment measures are only allowed as part of a multi-step treatment process (i.e., for pretreatment).

	Stormwater Treatment Measu	re (STM)	Hydraulic Sizing Criteria Used*	
				-
				1
*Key:	1a: Volume – WEF Method 1b: Volume – CASQA BMP Hand 2a: Flow – Factored Flood Flow M 2b: Flow – CASQA BMP Handboo 2c: Flow – Uniform Intensity Meth 3: Combination Flow and Volume ternative Certification: Was the	ethod ok Method ood Design Basis	m sizing and design reviewed by	a qualified thirc
	ty professional that is not a mem			. 1
	Yes ☐ No Name of Third-p	oarty Reviewer_		
A. B.	Property Owner's Name Responsible Party for Stormwat a. Name: b. Address: c. Phone/E-mail:		rdromodification Control O&M:	
Thi.	s section to be completed by Municipal	staff.		
Ind	&M Responsibility Mechanism licate how responsibility for O&M is	s assured. Check	all that apply:	
	O&M Agreement Other mechanism that assigns resp	oonsibility (describ	be below):	
intern	ection to be completed by Municipal sta al review and tracking process.) ewed By:	off (Note: This is an	optional section that agencies should m	odify per their
Community Development Department Public Works Departm			Public Works Department	
	Planning Division: Engineering:			
]]	Building Division:		Other (Specify):	
	Return form to: Data entry performed by:			

7. Stormwater Treatment Measure (STM) Sizing for Projects with Treatment Requirements